

# **S**hawver WELL COMPANY

## WATER WELL DRILLING AND REPAIRING

P. O. BOX 266

DIAL 515-237-5341

FREDERICKSBURG, IOWA 50630

February 27, 1978

Lauridsen Foods  
Britt, Iowa  
50423

### LOG OF WELL

	0'	to	4'	Topsoil
	4'	to	18'	Sticky Light-Blue Clay
	18'	to	25'	Light Blue Clay
	25'	to	72'	Dark Blue Sandy Clay
	72'	to	74'	Sand (Blue)
	74'	to	94'	Blue Clay Sticky
	94'	to	113'	Limerock Brown (Water @ 108')
	113'	to	115'	Shale
	115'	to	118'	Gray Limerock
	118'	to	135'	Shale
	135'	to	142'	Buff Limerock
	142'	to	143'	Buff Limerock with Shale
(made H <sub>2</sub> O)	143'	to	177'	Buff Limerock
	177'	to	179'	Buff Limerock with Shale
(made H <sub>2</sub> O)	179'	to	182'	Dark Brown Limerock
	182'	to	205'	White Limerock
	205'	to	278'	Brown Limerock
	278'	to	288'	Light Buff Limerock
	288'	to	295'	Dark Grey Limerock
	295'	to	300'	White Limerock with Shale
	300'	to	308'	Dark Grey Limerock
	308'	to	310'	Light Grey Limerock
	310'	to	314'	White Limerock with Shale
	314'	to	316'	Dark Blue Limerock
	316'	to	318'	Light Brown Limerock
	318'	to	325'	Shale, Varing Colors
	325'	to	335'	Medium Brown Limerock
	335'	to	340'	Shale
	340'	to	405'	Limerock Brown & Grey
(made H <sub>2</sub> O)	405'	to	420'	Buff Limerock
	420'	to	440'	Grey Limerock
	440'	to	460'	White Limerock
	460'	to	475'	White & Gray Limerock
	475'	to	477'	White Limerock

The well is cased to 133 feet ground level, with 135 feet of 8 inch Outside-Diameter casing, equipped with an 8 inch forged steel drive shoe.

The static water level is 35 feet. —

The recommended pump setting is 124 feet and pumping at the rate of 335 gallons per minute.

*MS*