

Shawver Well Co., Inc.
 Dyersville, IA
 Fredericksburg, IA
 PH: 800-568-4449

id 3075 well number 7906100
 owner name LAURIDSEN FOODS
 second name
 address 1
 address 2
 city/state BRITT, IA
 zip
 start date 06/01/79
 end date
 county Hancock
 township 3« WEST of BRITT ON HWY18
 section
 quarters
 s w l
 r p s
 water test inf

LOG OF WELL

0'	to	5'	Topsoil
5'	to	47'	Clay
47'	to	50'	Sand
50'	to	84'	Clay
84'	to	275'	Limerock
275'	to	440'	Brown limerock & some shale
440'	to	464'	White limerock

DESCRIPTION OF WELL

The well is cased to 86'3" with 16" OD x .312 wall steel casing. A 15' open hole was drilled to 275'. From 275' to 464', an 11 7/8" hole was drilled.

** See test pumping

BOREHOLE DATA

driller Henry Dawson

Shawver WELL COMPANY INC.

WATER WELL DRILLING AND REPAIRING

P.O. BOX 266

DIAL 319-237-5341

FREDERICKSBURG, IOWA 50630

LAURIDSEN TEST PUMPING RECORD Britt, Iowa

JUNE 25, 1979

1:10	280 gallons	31 feet 6 inches
1:20	280 gallons	42 feet
1:30	285 gallons	48 feet
2:00	285 gallons	49 feet
2:15	480 gallons	49 feet
2:30	480 gallons	68 feet
2:40	480 gallons	70 feet
2:45	620 gallons	85 feet
3:00	620 gallons	86 feet 4 inches
3:15	743 gallons	115 feet
3:30	743 gallons	114 feet 8 inches
4:00	743 gallons	115 feet 6 inches

JUNE 26, 1979

STATIC WATER LEVEL AT 100 A.M. was 32 feet 3 inches

10:00	488 gallons	63 feet 2 inches
10:09	668 gallons	88 feet
10:15	743 gallons	106 feet 5 inches
10:20	732 gallons	107 feet 8½ inches
10:30	726 gallons	109 feet 11 inches
10:45	726 gallons	111 feet 7½ inches
11:00	726 gallons	112 feet 9 inches
11:15	726 gallons	113 feet 9 inches
11:30	726 gallons	113 feet 6½ inches
11:45	726 gallons	113 feet 8 inches
12:00	723 gallons	114 feet
12:15	723 gallons	114 feet 2 inches
12:30	723 gallons	114 feet 5 inches
12:35	865 gallons	123 feet 8 inches
12:55	810 gallons	131 feet 5 inches
1: 00	810 gallons	133 feet 4 inches

DURING THE TEST PUMPING THE PUMP WAS SET AT 160 feet.

LAURIDSEN FOODS
Britt, Iowa 50423

June 25, 1979

LOG OF WELL

25506

0'	to	5'	Topsoil
5'	to	47'	Clay
47'	to	50'	Sand
50'	to	84'	Clay
84'	to	135'	Limerock
135'	to	275'	Limerock
275'	to	440'	Brown Limerock & some shale
440'	to	464'	Limerock White

CSD: 86' & 3" W/ 16-inch 5/16" Wall casing.