

SLESSOR, GERALD
R. R. #1
Nashua, Iowa

Chickasaw, Bradford, Sec. 4 SE $\frac{1}{2}$ SW $\frac{1}{2}$
Campground next to Little Cedar
July 11-19, 1983

A

w 36 284

94-14w

LOG OF WELL			
0'	to	35'	Sand
35'	to	45'	Blue clay
45'	to	80'	Sandy blue clay
80'	to	90'	Blue clay
90'	to	100'	Fine sand
100'	to	105'	Medium sand
105'	to	115'	Sand and shale

The well is cased to 98' with 7" O.D. x 6 3/8" I.D. x .317 wall T&C casing equipped with a forged steel drive shoe on end of casing. The well is equipped with a 5' Johnson #10 slot stainless steel screen installed from 98' to 103' with a 15' tailpipe and 10' riser pipe with the riser pipe equipped with a rubber packer. A 10" hole was drilled to 20' and cement

OVER

grout installed in the annular space.

The well is a flowing well with a free flow of 30 plus gpm.

TOM

P. 2
Gerald
Slessor

id 4708 well number 8307090
 owner name GERALD SLESSOR
 secnd name CAMPGROUND NEXT TO LITTLE
 CEDAR
 address 1 RR 1
 address 2
 city/state NASHUA
 zip 50658
 start date 07/11/83
 end date 07/19/83
 county Chickasaw
 township BRADFORD
 section 04
 quarters SESW
 s w l
 r p s
 water test inf

LOG OF WELL

0'	TO	35'	SAND
35'	TO	45'	BLUE CLAY
45'	TO	80'	SANDY BLUE CLAY
80'	TO	90'	BLUE CLAY
90'	TO	100'	FINE SAND
100'	TO	105'	MEDIUM SAND
105'	TO	115'	SAND AND SHALE

DESCRIPTION OF WELL

The well is cased to 98' with 7' OD x 6 3/8' ID x .317 wall T&C casing equipped with a forged steel drive shoe on end of casing. The well is equipped with a 5' Johnson #10 slot stainless steel screen installed from 98' to 103' with a 15' tailpipe and 10' riser pipe with the riser pipe equipped with a rubber packer. A 10' hole was drilled to 20' and cement grout installed in the annular space. The well is a flowing well with a free flow of 30 plug GPM.

BOREHOLE DATA

driller TOM ROCHFORD