Well Information-Drift Wells



Layne-Western Company, Inc.

WATER SUPPLY CONTRACTORS

705 SO. DUFF AVE.

: AMES, IOWA 50010

Phone 515 232-3563

Name of Job City of Hampton			
City or Village Hampton	· .	StateI	owa
Well No.: 4 Drillers: Rich Pe	jsha		
Well Location:ft. () and	ft. () of the	corner of
Section, Twp(), Range	()		County.
Otherwise located as West edge of pistol	l range - 30' Ea	ast from Wes	st fence.
Work Began: 3/1/71 Work Completed All measurements made from existin Casing Record:		ell Depth: Scre	
Amount Dia. Wt. or Thickness Material			
341 16" #3 Gauge ARMCO			
31' 24" 3/8" Steel	_with_welded_joints	from 21 ab.	gr_{to} 29' fr.
Screen Record: Type Layne Shutter - 1	<u>1</u> 34		
Amount Dia. Opening Material			
<u>20' 16" #5 SS</u>	_witWelded_joints	from 51!	to31!
	_withjoints	from	to
Type of Seal at Bottom SS Plate			
Hole Kecord:			
36" inch from 201	to54 !		
40 inch from 0	to201		
Gravel Pack Record:			
Amount Size Sou	Source		To
. <u>13.5</u> #3 Muscat	ine	291	51 '
Cementing Record: Top 291 is cemented	•		
Backfill Record: Gravel Pack from 29' to	51'		
LW- 33 SEE OTI	HER SIDE		

WELL LOG

19.7

Feet		Feet	Description
0	to	2	Black Soil
21	to	23	Yellow Brown Clay Till
23	to	28	Gray Clay Till with Layers of gravel
			Med. to coarse Gray sand and Gravel
			Blue gray Clay Till
	to		
	to		
	to பூ		
7		•	
;		i	
			-
-			
	to		
	to		
	to		evel. 71; pumping level 131 after 8 hours pumping at 250 g.p.m.
Well Tes	st Data	: Static L o	evel/_; pumping level after nours pumping at g.p.m.
Length of REMARI		8	hrs. See Well Test Data Sheet Dated3/11/71
			. :