

THORPE WELL COMPANY
1903 HULSIZER
ANKENY, IOWA

Drilled for Osceola Co. Rural Water at Peterson, Iowa
 Well is located _____ miles N-E-S-W and _____ miles N-E-S-W from _____
 in the _____ N _____ S Section _____ Township _____ Range _____
 Drilling started December 19 81 Completed December 19 81
Florine East well
 Well No. 3 Kind of Well Gravel pack Depth 30' Size hole started 24"
24" G. P. M. 282 Static Head 9' 2" Pumping level from surface 20' 5"
 Water was first encountered at 9' in sand Approx. Amt. _____ Temp. _____
 Remarks _____

(GIVE DETAILS OF PERFORATED PIPE AND SEALS)

RECORD OF PERMANENT PIPE					TEMPORARY PIPE	
SIZE OF PIPE	AMOUNT OF PIPE	DEPTH TO BOTTOM OF PIPE	DEPTH TO TOP OF PIPE	MAKE OF PIPE	SIZE OF PIPE	AMOUNT
12"	20'	20'	0'	steel casing		
12"	10'	30'	20'	Stainless steel Johnson screen	.080 slot	

Driller Jim Lacey From Surface to _____ feet
 Driller _____ From _____ feet to _____ feet
 Driller _____ From _____ feet to _____ feet

AMOUNT IN FEET	KIND OF SOIL OR FORMATION (BE SPECIFIC)	TOTAL DEPTH FEET
0	Silt	3
3	Dirty gravel	6
4	Black clay	10
4	Black sand	14
16	Coarse gravel w/rocks	30