Northway Well and Pump Co.

4895 8th Avenue Marion, Iowa 52302 Phone 319/377-6339

Drilling started June 25 19 97 Completed June 29 19	Hed for Muscatine Po		ater	M1	uscati	ne, Iowa	
in the			miles N-E-S-	W from			
	he 14 14 Sec	ion 16	Township_	76N Range	21	W	
Well No. #35 Kind of Well Reverse Rotar Depth 131' Size hole started 36	lling started June 25		19 <u>97</u> Com	pletedJune	29		9
	Il No. #35 Kind of Well_I	Reverse Ro	tar Bepin_	131'	Size hole sta	36	in
Finish 36" G. P. M. Static HeadPumping level from surface							
Water was first encountered at 15' in Approx. Amt Temp Temp	iter was first encountered at 1!	in		Approx1mt		Temp	
Remarks Casing cement grouted from 20' to 5' below Ground les	marks Casing Cement	grouted	from	20' to 5'	below	Ground 1	eve
(GIVE DETAILS OF PERFORATED PIPE AND SEALS)							-
RECORD OF PERMANENT PIPE TEMPORARY PIPE	RECORD OF PERMANENT PIPE			TEMPORARY PIPE			
SIZE AMOUNT DEPTH TO DEPTH TO TOP OF PIPE MAKE OF PIPE SIZE AMOUNT	하나 이 아이지 않는 그 그는 그를 가는 것이 되었다.			MAKE OF PIPE		AMOUNT	
24" 97' 4"	24" 97' 4" 97	4"	+2	.500 Stee1			
24" 35' 8" 133' 97' 4" .030 SS Screen	24" 35' 8" 13:	3' 9	7 ' 4"	.030 SS Scr	een		
Well was packed with #0 Gravel							
Driller Dan Glessner From Surface to 131'	Dan Glessner	<u>-</u>		_ From Surface 10	1	31'	_feri
Driller Tom Engelken From 0 feet to	Tom Engelker	1		_ FromO	feet 10	131'	_fee
1)riller feet to	riller			_ From	feet to		_feet
AMOUNT IN FEET KIND OF SOIL OR FORMATION (BE SPECIFIC) TOTAL DEPTH FEE	AMOUNT IN FEET	KIND OF SOIL	OR FORMATION	(BE SPECIFIC)		TOTAL DEPTH F	EET
Top soil and sand 5	Top soil and sand				5		
Fine to medium gravel, small boulders 40	Fine to medium gravel, small boulders				ers	40	
8 Fine brown sand 48						48	
Course brown sand with fine gravels 71	23 Cours	e brown sa	nd with	fine gravel	S	71	
				· · · · · · · · · · · · · · · · · · ·	Market		