65663

Layne

Layne-Western

65603

A Division of Layne Christensen Company 4601 N. 252nd Street, PO Box 597 Valley, Nebraska 68064 (409) 359-2049

Contact:	Regional	Water	_			_	Date:		10/25/2004	
City and S	State:	Avoca, Iowa_				_	Driller:	Duane Trask		_
Well No. N-15		_at test hole No.		2004-15	Well location (atta		tion (attach map)	North V	Vell Field	
Work com	npleted:			_ Number of	man-hours	s as charge	d to job on d	aily report:		_
Materials:		Length Diameter		Gauge or Wall Thickness			Туре		Number of Openings	
Screen:		5'	12	.375	SST		Johnson		.090	
Inner Casing:		24' 11"	8	.322	Carbon Steel		Livingston			
Outer Cas	sing:	pitless 7'								
6	_tons of gr	avel used in	the well.	Size:	AA		_			
Well Test	. Did you u	se test or per	e test or permanent pur		Test		Bowl Size:		Stages	
Size of or	ifice:		inch by		_inch.	Orifice tub	oe reading:		inches.	
Pumping	test (measuren	ments from ground-	·level)·			1			_	7
Time		Gallons Per Minute (GPM)		Static		Drawdown		Pumping Level		
				See Attac	hed Sheet	1		_		1
									_	-
Recovery in 5-minutes: Yes						, in 30)-minutes:			J
	eal bottom o		Yes	_ *	Thickness	:375	_inches.	Material:	SST	_
		From		feet to		feet,		feet to		- _feet.
If all scree	en was not p	placed at bot	tom, state I	now is was s	spaced.					
Fron	n	feet to		_ feet; from		feet to		feet; from		feet
te	0	_feet.								
Depth of v	well from gr	ound level to	top of plug	29'	*	Size of	f drilled hole:	30	inches.	
Was cem	ent placed	around or bet	ween any	of the casing	gs?	Yes	If so, stat	te where, ho	ow much	T
and meth	od used:	10' Cemen	t							

Layne-Western

A Division of Layne Christensen Company 4601 N. 252nd Street, PO Box 597 Valley, Nebraska 68064 (402) 359-2042

65603

WELL INFORMATION

CONTRA	ACT	Regional Water			WELL No.	N-15			
			.		DATE	10/25/200	4.		
Log of we	ll from gr	round level:					_		
	J								
Feet		Feet			Formation				
0	to	15	Clay						
15	to	29	Coarse sand and gravel						
29	to	30	Grey clay						
	to								
	to								
	to								
	to								
	to								
	to								
	to								
	to								
	to								
	to					_			
	to								
	to		2						
	to								
	to								
	to								
	to								
	to						_		
	to								
	ı					1			
	-			29' Dept <u>h</u>		→			
	•	29'	12' Gravel Pack	12' 10' H	12' 10' Holeplug 10'-0' Cement 7'-11"				
	ľ		Grout	Casing Extension					
30"	—	5' x 12" Scr	cen	3:	1'-11" Casing -				
Drilled Hole	← 0.37	<u> </u>		2000 1			Steel pidess		



Natural Ground Level